

3000 SERIES 3 POINT TOOLBAR



SPECIFICATIONS

- Hydraulic wing lift
- Telescoping and swinging rear hitch
- Hydraulic hose & gauge stand
- 30" of rank provides superior residue flow
- Available up to 58'6" working width
- Flat fold outer wing with mechanical lockdown
- Standard 1-1/4" quick coupler
- 6" X 6" or 6" X 4" Tubular Framework
- Pin adjust gauge wheels
- 1" x 2" or 1-1/4" x 2" Flat Shanks
- Warranty: 1 year on main frame
- Raven Metering System
- Spacers allow you to tune the bar's flexibility to your specific needs



OPTIONS

- Various disc sealers, coulters, knives, and shank clamp options available manufactured by Dalton Ag
- High speed row units
- Various row spacing options available
- Red, Blue, Green or Black Color options
- In-line transport with screw type gauge wheels
- Full manifold plumbing



Above shows our inline transport position with screw type gage wheels and wing lock up with tow tongue attached.



3-Point Hookup



Pull out and swing away wagon hitch



Dalton

AG PRODUCTS

Manufacturer of Fertilizer Application Equipment

602 E. Van Buren, Lenox, IA 50851

800.342.7498

Find your local Dalton Ag Dealer online

www.DaltonAg.com