

LIQUID FERTILIZER APPLICATOR *DLQ SERIES*

DLQ SERIES

MODELS AND OPTIONS
TO FIT YOUR OPERATION

NOW AVAILABLE
POWDER COAT
PAINT



Model DLQHD 11-15 Row Combo Applicator

Dalton 
AG PRODUCTS

VALUE FEATURES

- State-of-the-art powder coat paint.
- Superior ground clearance.
- Gull wing option available.
- Greaseless wing pivot points for longer life.
- Versatile custom row spacing options.
- Available in blue, red, green or black frame.


SIMPLE. DURABLE. AMERICAN.

LIQUID FERTILIZER APPLICATOR DLQ SERIES

APPLICATOR SPECIFICATIONS

FEATURES	DLQ	DLQHD	DELTA EDITION
Rows	7-17	11-23	15-23
Row spacing	30" standard custom spacing optional	30" standard custom spacing optional	30" or 38" adjustable custom spacing optional
Working width	Up to 42"	Up to 60'	Up to 60'
Center section width	10.7', 13', 15.5'	10.7', 13', 15.5'	13'
Toolbar frame	4"x6" tubing double row	4"x6" tubing double row	4"x 6" tubing double row
Crop clearance to toolbar frame when raised	49"	53"	56"
Liquid delivery mode	Injection or knife	Injection or knife	Injection or knife
Pump drive system	Ground drive OR Hydraulic drive	Ground drive OR Hydraulic drive	Hydraulic drive
Two-speed jack	Standard	Standard	Standard
Hitch	CAT 4 bull pull	CAT 4 bull pull	CAT 4 bull pull
Axle	120"	120"	80"-120" adjustable
Parallel linkage system	Standard	Standard	Standard
Wing folds			
21' toolbar	Single fold	n/a	n/a
27' toolbar	Single fold	Single fold	n/a
32' toolbar	Single fold	Single fold	n/a
35' toolbar	Single fold double fold optional	Single fold double fold optional	Double fold
42' toolbar	Double fold	Double fold	Double fold
60' toolbar	n/a	Triple fold	Triple fold
Tank size	500 to 1,000 gal.	1,000 to 2,000 gal.	1,500 gal.
Tires and wheels	320/90/R42	380/90/R46	380/90/R46
Greaseless primary wing pivot points	Standard	Standard	Standard
Hand Wash Station	Standard (3 gal.)	Standard (3 gal.)	Standard (3 gal.)
Light kit	Optional	Optional	Standard
Safety chain kit	Optional	Optional	Standard
Gull wing feature	Optional	Optional	Standard
Down pressure feature	Optional	Optional	Standard
Manual gauge wheels	Optional	Optional	Standard
Minimum HP requirement	>100 HP	>140 HP	>140 HP
Paint (available in red, blue, green, black)	Powder coat	Powder coat	Powder coat
Frame warranty	24 months	24 months	24 months

NEW DLQHD "DELTA EDITION"



80"-120" adjustable axle for 30" and 38" rows.



Steel reinforced 1,500 gallon narrow poly tank.



46" Duals for high clearance, less compaction.



DOT compliant full-width lighting kit standard.

Simple. Durable. American.

Dalton
AG PRODUCTS

602 E. Van Buren
Lenox, Iowa 50851

www.DaltonAg.com

office@daltonag.com

800.342.7498

100% EMPLOYEE OWNED