

ANHYDROUS AMMONIA TOOLBAR

D SERIES

Dalton
AG PRODUCTS



WORLD CLASS FEATURES

- Hydraulic Wing Lift
- Telescoping & Swinging Rear Hitch
- Hydraulic Hose & Gauge Stand
- Available working width up to 58'6"
- 30" Rank provides maximum residue flow
- 6"x4" Heavy Duty Tubular Framework

NOW AVAILABLE

POWDER COAT

PAINT

www.daltonag.com

SIMPLE. DURABLE. AMERICAN.

ANHYDROUS AMMONIA TOOLBAR

D SERIES

D SERIES (3 POINT) TOOLBAR SPECIFICATIONS		
FEATURES	CLASS 1	CLASS 2
Rows	9 to 13	15 to 23
Row Spacing	30" Standard (custom options)	30" Standard (custom options)
Custom Row Spacing	Optional	Optional
Inline Transport	Optional	Optional
Working Width	Up to 32'	Up to 55'
Center Section Width	13'	13', 14', 15.5', 16'
Frame Tubing	Standard: 4" x 6"	Standard: 4" x 6"
Rank	30"	30"
Hitch	CAT1 3 Point	CAT1 3 Point
HD Rear Hitch	Standard	Standard
Wing Sections	3 Sections	3 or 5 Sections
Quick Coupler Stand	Standard	Standard
Pin-Type Gauge Wheels	Standard	Standard
Greaseless Primary Pivot Points	Standard	Standard
Hydraulic Hose & Gauge Stand	Standard	Standard
Light Kit	Standard	Standard
2 Year Main Frame Warranty	Standard	Standard
Powder Coat Paint	Red, Black, Blue, Green	Red, Black, Blue, Green

CUSTOMIZE YOUR
3-POINT TOOLBAR
WITH DALTON DISC SEALERS



STANDARD



HEAVY DUTY

ADDITIONAL OPTIONS

- High Speed Row Units
- Various Row Spacing Options
- In-Line Transport Configuration
- Colors: Red, Blue, Green, Black



OPTIONAL
IN-LINE TRANSPORT POSITION



3-POINT BAR HOOK-UP



3-POINT BAR REAR HITCH

Manufactured by:

Dalton
AG PRODUCTS

MOBILITY
BY DALTON AG



602 E. Van Buren
Lenox, Iowa 50851

office@daltonag.com

1-800-342-7498

www.DaltonAg.com

SEE YOUR LOCAL DEALER

