

LIQUID FERTILIZER APPLICATOR

Dalton
AG PRODUCTS



STEALTH

LIQUID APPLICATORS



EXCLUSIVE FEATURES

- ◆ HEAVY DUTY STEEL TUBE FRAME
- ◆ SUPERIOR GROUND CLEARANCE
- ◆ GULL WING (OPTIONAL)
- ◆ GREASELESS WING PIVOT POINTS
- ◆ VERSATILE CUSTOM ROW SPACING OPTIONS

DURABLE · RELIABLE
AMERICAN



DALTON AG
LIQUID APPLICATORS

LIQUID FERTILIZER APPLICATOR

STEALTH

LIQUID APPLICATORS

STEALTH SERIES LIQUID FERTILIZER APPLICATOR

FEATURES	STEALTH	STEALTH PRO	STEALTH ELITE
Rows	11 to 15	11 to 23	11 to 23
Row Spacing	Standard: 30"	Standard: 30" Custom Spacing Available	Standard: 30" Custom Spacing Available
Working Width	Up to 35'	Up to 60'	Up to 60'
Center Section Width	10.7', 13', 15.5'	10.7', 13', 15.5'	10.7', 13', 15.5'
Toolbar Frame	7" x 7" Steel Tubing (Single Row)	4" x 6" Steel Tubing (Double Row)	4" x 6" Steel Tubing (Double Row)
Bar	11 Knife or 11-15 Knife combo	11-15 Knife combo 13-17 Knife combo 23 Knife	11-15 Knife combo 13-17 Knife combo 23 Knife
Crop Clearance to Toolbar Frame when Raised	49"	53"	53"
Liquid Delivery Mode	Injection or Knife	Injection or Knife	Injection or Knife
Pump Drive System	Ground Drive or Hydraulic Drive	Ground Drive or Hydraulic Drive	Ground Drive or Hydraulic Drive
Two-Speed Jack	Standard	Standard	Standard
Hitch	CAT4 Bull Pull	CAT4 Bull Pull	CAT4 Bull Pull
Axle	120"	120"	120"
Parallel Linkage System	Standard	Standard	Standard
Tank Type	Cone Bottom	Cone Bottom	Drainable
Tank Size	1,000 Gallon	1,300 or 1,750 Gallon	1,610 or 2010 Gallon
Tires & Wheels	320/90/R46	380/90/R46 VF 380/90 R46 - 1,750 tank	VF 380/90 R46
Greasless Primary Wing Pivot Points	Standard	Standard	Standard
Hand Wash Station	Standard: 3 Gallon	Standard: 3 Gallon	Standard: 3 Gallon
Light Kit	Standard	Standard	Standard
Gull Wing Feature	Optional	Optional Standard on 23 row	Optional Standard on 23 row
Down Pressure Feature	Optional	Optional	Optional
Manual Gauge Wheels	Optional	Optional	Optional
Frame Warranty	24 Months	24 Months	24 Months
Powder Coat Paint	Black	Black	Black

CUSTOMIZE YOUR NEW DLQ LIQUID APPLICATOR TO FIT YOUR NEEDS

- Optional Gull Wing
- Optional Down Pressure
- Optional Manual Gauge Wheels
- Custom Spacing Available
- Hydraulic or Ground Driven Pump



Available Models

STEALTH SERIES

-1,000 cone bottom

STEALTH PRO

-1,300 OR 1,750 cone bottom

STEALTH ELITE

-1,610 or 2,010

norwesco drainable tank



Stealth Elite

Manufactured by:



602 E. Van Buren
Lenox, Iowa 50851



office@daltonag.com



1-800-342-7498



www.DaltonAg.com

SEE YOUR LOCAL DEALER

