

MOBILITY

BY DALTON AG

DRY FERTILIZER SPREADERS



ROW CROP
WIDE SPREAD

ROW CROP WIDE SPREAD

X2

TANDEM

MOBILITY 100



WWW.DALTONAG.COM



DURABLE. RELIABLE. AMERICAN.

YOU'VE BUILT YOUR
LIFE ON HARD WORK.

WE'VE BUILT OUR
NAME ON IT.



WWW.DALTONAG.COM



Our Mission

“Dalton Ag will be the market leader in the categories in which we compete, partnering with our customers and consistently meeting their needs with on-time delivery of high-quality products and services. Recruiting, training and retaining highly committed and passionate employees who are totally responsive to our customers will be the cornerstone of our success.”

Dalton 
AG PRODUCTS

MOBILITY
BY DALTON AG



ROW CROP SERIES

WIDE SPREAD

MODELS AVAILABLE: 600, 800, 1000, 1200

With various options and four models to choose from, the Mobility by Dalton Row Crop Series is the premiere piece of equipment for sidedressing nitrogen on corn early in the growing season.



Mobility Row Crop: 600 (6 Ton)



Mobility Row Crop: 800 (8 Ton)

ROW CROP SPECIFICATIONS

6 & 8 TON

WIDE SPREAD SERIES SPREADER SPECIFICATIONS		
FEATURES	MOBILITY 600	MOBILITY 800
Capacity (Weight)	6 Tons	8 Tons
Hopper Length	120"	120"
Hopper Width	93"	93"
Hopper Capacity (Volume)	200 cu. ft.	270 cu. ft.
Overall Length	230"	230"
Overall Height	107"	120"
Overall Width	96"	96"
Empty Weight	4,000 lbs.	5,200 lbs.
Groud Clearance	45" under Spinners	45" under Spinners
	37" under Frame	37" under Frame
Spread Pattern	Up to 90'	Up to 90'
Hopper Construction	409 Stainless Steel	409 Stainless Steel
Spinner Drive System	540/1000 PTO: Standard Tractor Hydraulic: Optional 10 gpm req	540/1000 PTO: Standard Tractor Hydraulic: Optional 10 gpm req
Spinners	Dual Gearbox Driven	Dual Gearbox Driven
Hitch	HD Clevis: Standard	HD Clevis: Standard
	CAT4 Bull Pull: Optional	CAT4 Bull Pull: Optional
Axle	72" - 120" adjustable	80" - 120" adjustable
Conveyor Drive	2 SPD Ground Drive or Hydraulic -10 gpm req	2 SPD Ground Drive or Hydraulic -10 gpm req
SRT Roll Tarp	Standard	Standard
Tires & Wheels	320/90/R42	380/90/R46
Light Kit	Standard	Standard
Variable Rate Ready	Optional	Standard
Scale Kit with Monitor	Optional	Optional
Standard Powder Coat Paint Colors	White	White
Warranty	24 Months	24 Months



» SCAN ME
For Pictures & Video

ROW CROP SPREADERS

MOBILITY
BY DALTON AG

ROW CROP SERIES

WIDE SPREAD

MODELS AVAILABLE: 600, 800, 1000, 1200

With various options and four models to choose from, the Mobility by Dalton Row Crop Series is the premiere piece of equipment for sidedressing nitrogen on corn early in the growing season.



Mobility Row Crop: 1200 (12 Ton) with row crop tires



Mobility Row Crop: 1000 (10 Ton) with the optional dual tires



Mobility Row Crop: 1200 (12 Ton) with the optional floater tires

ROW CROP SPECIFICATIONS

10 & 12 TON

WIDE SPREAD SERIES SPREADER SPECIFICATIONS		
FEATURES	MOBILITY 1000	MOBILITY 1200
Capacity (Weight)	10 Tons	12 Tons
Hopper Length	152"	152"
Hopper Width	102"	102"
Hopper Capacity (Volume)	335 cu. ft.	400 cu. ft.
Overall Length	263"	263"
Overall Width	102"	128" (Floaters)
Overall Height	121"	128"
Groud Clearance	45" under Spinners 37" under Frame	45" under Spinners 38" under Frame
Spread Pattern	Up to 90°	Up to 90°
Hopper Construction	409 Stainless Steel	409 Stainless Steel
Spinner Drive System	Tractor Hydraulic: Optional 10 gpm req	Tractor Hydraulic: Optional 10 gpm req
Spinners	Dual Gearbox Driven	Dual Gearbox Driven
Hitch	CAT4 Bull Pull	CAT4 Bull Pull
Axle	82" - 120" adjustable	82" - 120" adjustable
Conveyor Drive	Hydraulic -10 gpm req	Hydraulic -10 gpm req
SRT Roll Tarp	Standard	Standard
Tires & Wheels	380/90/R46 Duals: Optional Floaters: 850/50 R30.5 Optional	VF 380/90/R46 Duals: Optional Floaters: 850/50 R30.5 Optional
Light Kit	Standard	Standard
Variable Rate Ready	Optional	Standard
Scale Kit with Monitor	Optional	Optional
Standard Powder Coat Paint Colors	White	White
Warranty	24 Months	24 Months



» SCAN ME
For Pictures & Video

ROW CROP SPREADERS

MOBILITY
BY DALTON AG

X2 SERIES

WIDE SPREAD

MODELS AVAILABLE: 1055, 1064

BIN CONFIGURATIONS: 50/50, 60/40

With multiple bin configurations and a 333cu.ft. capacity, the Mobility by Dalton X2 Series is the premiere piece of equipment for variable rating two products at once.



1064 - 60/40 Bin



1055 - 50/50 Bin



X2

SPECIFICATIONS

X2 SPREADER SPECIFICATIONS		
FEATURES	X2 1055	X2 1064
Bin Configurations	50/50	60/40
Capacity (Weight)	10,000 lbs. Front Bin 10,000 lbs. Rear Bin	12,000 lbs. Front Bin 8,000 lbs. Rear Bin
Hopper Length	76 1/8" Front Bin 100 3/8" Rear Bin	93" Front Bin 83 5/8" Rear Bin
Hopper Width	93"	93"
Hopper Capacity (Volume)	166.67 FT ³ Front Bin 166.67 FT ³ Rear Bin	203.67 FT ³ Front Bin 139.13 FT ³ Rear Bin
Overall Length	286"	286"
Overall Height	120"	120"
Overall Width	96"	96"
Groud Clearance	45" under spinners 37" under frame	45" under spinners 37" under frame
Spread Pattern	Up to 90'	Up to 90'
Hopper Construction	409 Stainless Steel	409 Stainless Steel
Spinner Drive System (PMW Valve)	Tractor Hydraulic 10 gpm req	Tractor Hydraulic 10 gpm req
Spinners	Dual Gearbox Driven	Dual Gearbox Driven
Jack	5,000 lbs.	5,000 lbs.
Hitch	CAT4 Bull Pull	CAT4 Bull Pull
Axle	80" - 120" adjustable	80" - 120" adjustable
Conveyor Drive (PMW Valve)	Hydraulic 10 gpm req	Hydraulic 10 gpm req
SRT Roll Tarp	Standard	Standard
Tires & Wheels	380/90 R46: Standard Duals: Optional Floaters 850/50 - 30.5: Optional	380/90 R46: Standard Duals: Optional Floaters 850/50 - 30.5: Optional
Light Kit	Standard	Standard
Variable Rate ISO Ready	Standard	Standard
Two Camera System w/ 10" monitor	Standard	Standard
Back Up Camera	Optional	Optional
Scale Kit with Monitor	Optional	Optional
Standard Powder Coat Paint Colors	White	White
Warranty	24 Months	24 Months



» **SCAN ME**
For Pictures & Video

X2 SPREADERS

MOBILITY
BY DALTON AG

TANDEM SERIES

WIDE SPREAD

MODELS AVAILABLE: 500, 600, 800

PERFECT FOR RUGGED TERRAIN

The Mobility Tandem Series is excellent for scaling ditches, culverts and more due to its "walking" design. This axle will give you the most flexibility when working on rugged, uneven terrain.



Mobility Tandem Series: 800 (8 Ton)



Mobility Tandem Series: 600 (6 Ton)
Optional Fitted Tarp



Mobility Tandem Series: 500 (5 Ton)

FIND A DALTON DEALER
NEAR YOU!

WWW.DALTONAG.COM

TANDEM SPECIFICATIONS

TANDEM SERIES SPREADER SPECIFICATIONS			
FEATURES	500	600	800
Class	Full Size	Full Size	Full Size
Capacity (Weight)	5 Tons	6 Tons	8 Tons
Hopper Capacity (Volume)	170 cu. ft.	200 cu. ft.	270 cu. ft.
Hopper Length	120"	120"	120"
Hopper Width	93"	93"	93"
Overall Length	220"	220"	220"
Overall Height	73"	83"	93"
Overall Width	96"	96"	96"
Empty Weight	2,800 lbs.	3,100 lbs.	4,000 lbs.
Spread Pattern	40', 50'	40', 50'	40', 50'
Hopper Construction	409 Stainless Steel	409 Stainless Steel	409 Stainless Steel
Spinner Drive System	Standard: 540 PTO Optional: 540/1000 Optional: Tractor Hydraulic 4 gpm req	Standard: 540 PTO Optional: 540/1000 Optional: Tractor Hydraulic 4 gpm req	Standard: 540 PTO Optional: 540/1000 Optional: Tractor Hydraulic 4 gpm req
Conveyor Drive System	2-SPD Ground Drive Optional: Hydraulic 4 gpm req	2-SPD Ground Drive Optional: Hydraulic 4 gpm req	2-SPD Ground Drive Optional: Hydraulic 4 gpm req
Hydraulic On/Off for Ground-Drive Conveyor	Standard	Standard	Standard
Spinners	Dual Gearbox Driven	Dual Gearbox Driven	Dual Gearbox Driven
Jack	5,000 lbs.	5,000 lbs.	5,000 lbs.
Hitch	Standard: HD Clevis Optional: CAT4 Bull Pull	Standard: HD Clevis Optional: CAT4 Bull Pull	Standard: HD Clevis Optional: CAT4 Bull Pull
Axle	Walking Beam	Walking Beam	Walking Beam
60" Track	Optional	Optional	N/A
Hydraulic Surge Brakes	Optional: 2 & 4 Wheel Brakes	Optional: 2 & 4 Wheel Brakes	Optional: 2 & 4 Wheel Brakes
Tires	12.5 L x 15 / 6 Bolt	16.5 L x 16.1 / 8 Bolt	19 L x 16.1 / 8 Bolt
Light Kit	Standard	Standard	Standard
Variable Rate Ready	Optional	Optional	Optional
SRT Roll Tarp	Optional	Optional	Optional
Standard Powder Coat Paint Colors	White	White	White
Warranty	24 Months	24 Months	24 Months



▶ **SCAN ME**
For Pictures & Video

TANDEM SPREADERS

M·OBILITY
BY DALTON AG

100 (1 Ton)

GREAT FOR SMALL ACREAGES
AND MORE!



VINEYARDS

GOLF COURSES

FOOD PLOTS

TURF/LAWN CARE

ORCHARDS

SMALL ACREAGES

100 (1 TON) SPECIFICATIONS

100 SPREADER SPECIFICATIONS	
FEATURES	
Capacity (Weight)	1 Ton
Hopper Capacity (Volume)	33 cu. ft.
Hopper Length	72"
Hopper Width	45 5/8"
Overall Length	137"
Overall Height	66"
Overall Width	68"
Empty Weight	1,320 lbs.
Wheel Track	55 1/2"
Spread Pattern	40'
Hopper Construction	409 Stainless Steel
Spinners	Dual Gearbox Driven
Jack	5,000 lbs.
Hitch	Clevis
Axle	Single
Tires	11 L x 15 / 6 Bolt
Standard Powder Coat Paint Colors	White
Warranty	24 Months
Options	
Spinner Drive System	Standard: 540 PTO Optional: Tractor Hydraulic 4 gpm req
Conveyor Drive System	2-SPD Ground Drive Optional: Hydraulic 4 gpm req
Hydraulic On/Off for Ground-Drive Conveyor	Optional
Light Kit	Optional
Variable Rate Ready	Optional
SRT Roll Tarp	Optional
Stainless Steel Bander	Optional
Hopper Extension	Optional: to 1.5 Ton (50 cu. Ft.)



» SCAN ME
For Pictures & Video

100 SPREADERS

MOBILITY
BY DALTON AG

M·BILITY

BY DALTON AG



**VARIOUS TYPES OF SPREADERS
TO FIT YOUR NEEDS!**

**FIND YOUR LOCAL DALTON DEALER AT:
WWW.DALTONAG.COM**

Dalton

AG PRODUCTS



YouTube

M·OBILITY BY DALTON AG



NH3 Toolbars



Dry Spreaders



NH3 Running Gears



Liquid Applicators



Nurse Trailers

VIEW DALTON AG'S FULL PRODUCT LINE AT:
WWW.DALTONAG.COM



**WHEN THE WORK IS HARD,
THE CHOICE IS SIMPLE.**

MOBILITY
BY DALTON AG



MANUFACTURED BY DALTON AG, INC.
602 E. VAN BUREN ST. LENOX, IA 50851
1-641-333-4518 OFFICE@DALTONAG.COM